

REXP-1210U-RP	
Host Interface	Three SAS 6Gbps 4x wide port (SFF-8644)
Drive Bay	12 x 3.5-inch SATA 6Gb/s, 3Gb/s hard drive or 2.5-inch SATA SSD
LED Indicators	Front panel: Status, fault, system over heat, fan error Rear panel: SAS link, SAS error, enclosure ID
Form Factor	2U rackmount
Dimensions (H x W x D)	88 x 439 x 520 mm 3.46 x 17.28 x 20.47 inch
Weight	Net weight (NAS only): 14.8 kg/ 32.63 lb Gross weight (with packing and accessories):21.99 kg/ 48.48 lb
Sound Level	Sound pressure (LpAm): 46.1 dB(A)
Operating Temperature & Relative Humidity	0 ~ 40°C (32°F ~ 104°F), 5 ~ 95% RH non-condensing, wet bulb: 27°C (80.6°F)
Power Consumption (W)	In Operation 162.47 W
Power Supply Unit	Redundant/Hot Swap ATX Power Supply, 400 W, 90-264 Vac~, 47-63 Hz
Fan	3 x 6 cm smart cooling fan (hot-swappable fan module)

Note: Use only QNAP memory modules to maintain system performance and stability. For NAS devices with more than one memory slot, use QNAP modules with identical specifications. Warning: Using unsupported modules may degrade performance, cause errors, or prevent the operating system from starting.

* Sound Level Test Environment: Refer to ISO 7779; Maximum HDD loaded; Bystander Position; Average data from 1 meter in front of operating NAS.

Designs and specifications are subject to change without notice.