

TS-2888X-W2195-256G	
CPU	Intel® Xeon® W-2195 18-core 2.3 GHz Processor (burst up to 4.3 GHz)
CPU Architecture	64-bit x86
Floating Point Unit	Yes
Encryption Engine	Yes (AES-NI)
System Memory	256 GB RDIMM DDR4 ECC (8 x 32GB)
Maximum Memory	512 GB (8 x 64GB)
Memory Slot	8 x DDR4 RDIMM/LRDIMM  IMPORTANT: You can only use one type of dual in-line memory module (DIMM) at a time. Do not use registered DIMM (RDIMM) with unbuffer DIMM (UDIMM) memory.
Flash Memory	4GB (Dual boot OS protection)
Drive Bay	8 x 3.5-inch + 20 x 2.5-inch
Drive Compatibility	3.5-inch bays: 3.5-inch SATA hard disk drives 2.5-inch SATA hard disk drives 2.5-inch SATA solid state drives  2.5-inch bays: U.2 slot: 2.5-inch U.2 NVMe Gen3 x4/x2 solid state drives SATA slot: 2.5-inch SATA solid state drives
Hot-swappable	Yes
SSD Cache Acceleration Support	Yes
Gigabit Ethernet Port (RJ45)	4
10 Gigabit Ethernet Port	2 x 10GBASE-T
Jumbo Frame	Yes
PCIe Slot	8 Slot 1: PCIe Gen3 x8 or x4 (CPU) Slot 2: PCIe Gen3 x4 (CPU) Slot 3: PCIe Gen3 x8 or x4 (CPU) Slot 4: PCIe Gen3 x4 (CPU) Slot 5: PCIe Gen3 x8 or x4 (CPU) Slot 6: PCIe Gen3 x4 (CPU) Slot 7: PCIe Gen3 x4 (PCH) Slot 8: PCIe Gen3 x4 (PCH)  Slot 1, 3, 5 provides the width of PCIe Gen.3 x8 when slot 2, 4, 6 is not in use. Slot 1, 3, 5 then provides the width of PCIe Gen.3 x4 only when an expansion board is installed in slot 2, 4, 6.
USB 2.0 port	4

USB 3.0 port	6
Audio Input	2 x 3.5mm microphone jacks (dynamic microphones only)
Audio Output	speaker, 3.5mm line out jack (for amplifier or headphone amplifier)
Form Factor	Tower
LED Indicators	3.5-inch HDD, 2.5-inch SSD, 2.5" U.2 SSD, Status, LAN, USB port status
LCD Display/ Button	Yes
Buttons	Power, Reset, USB Copy
Dimensions (HxWxD)	612 × 374 × 448 mm
Weight (Net)	26.7 kg
Weight (Gross)	31.46 kg
Operating temperature	0 - 40 °C (32°F - 104°F)
Relative Humidity	5-95% RH non-condensing, wet bulb: 27°C (80.6°F)
Power Supply Unit	2000W PSU, 200-240Vac
Fan	1 x 9 cm fan (12V DC) 9 x 12 cm fan (12V DC)
Sound Level	33.6 db(A)

Note: Use only QNAP memory modules to maintain system performance and stability. For NAS devices with more than one memory slot, use QNAP modules with identical specifications. Warning: Using unsupported modules may degrade performance, cause errors, or prevent the operating system from starting.

\* Sound Level Test Environment: Refer to ISO 7779; Maximum HDD loaded; Bystander Position; Average data from 1 meter in front of operating NAS.

Designs and specifications are subject to change without notice.