TVS-882BRT3-RDX-i7-32G (By Request)

Procesor	Intel® Core™ i7-7700 Quad-core 3.6 GHz (Max. 4.2 GHz)
Karta graficzna	9th Intel® HD Graphics
Pamięć systemowa	32GB DDR4 (8GB x 4)
Gniazdo pamięci	4
Maksymalna pojemność pamięci	64GB
Pamięć flash	512MB DOM
Gniazdo dysku M.2 SSD	2 x M.2 2242/2260/2280/22110 SATA 6Gb/s SSD Note: 1. The M.2 SSD is not included as standard. 2. M.2 SSD operations can easily generate excessive heat. It is recommended to install a heatsink (from QNAP or a third-party provider) on the M.2 SSD.
Wnęka dysków	8 x 2.5”/3.5” SATA 6Gb/s, 3Gb/s HDD or SSD
Port Thunderbolt	4 x Thunderbolt™ 3 high-speed port
Port USB	1 x USB 3.0 port (Front) 4 x USB 3.0 port (Rear)
Port Gigabit sieci Ethernet	4 x GbE RJ45
Wyjście HDMI	3 (HDMI 1.4b)
Gniazdo PCIe	3 (HDD area: 1* PCIe Gen3 x8; Processor area: 2* PCIe Gen3 x4)
Dźwięk	Input: 2 x 6.3mm MIC In Output: 2 x built-in speakers and 1 x 3.5mm Line Out
Wymiary (wys. x szer. x głęb.)	234.6 (H) x 369.9 (W) x 319.8 (D) mm 9.23 (H) x 14.56 (W) x 12.59 (D) inch
Waga	Net: 11.23 kg (24.76 lbs) Gross (with packing and accessories): 12.32 kg (27.16 lbs) ODD Preloaded: 0.63kg/ 1.4 lb
Poziom dźwięku	Sound pressure (LpAm) (bystander position): 21.6 dB (with 8 x Seagate ST2000VN000-1HJ164 Hard Drive installed)
Zasilacz	ATX 100-240V~, 3-1.5A Output 250W
Wentylator	System Area: 3 x 8 cm cooling Fan Processor Area: 2 x 9 cm Fan

Note: Use only QNAP memory modules to maintain system performance and stability. For NAS devices with more than one memory slot, use QNAP modules with identical specifications. Warning: Using unsupported modules may degrade performance, cause errors, or prevent the operating system from starting.

* Sound Level Test Environment: Refer to ISO 7779; Maximum HDD loaded; Bystander Position; Average data from 1 meter in front of operating NAS.

Designs and specifications are subject to change without notice.